

# TECHNICAL DATA SHEET



PRODUCT CODE: CBMT2415

Fabric Construction: COMBI MAT FABRIC

## GLASS FIBER SPECIFICATION

GLASS TYPE	E Glass	
TOTAL AREA WEIGHT	38.50 oz/sq. yd ( $\pm 5\%$ )	1305 g/sq.m ( $\pm 5\%$ )
FABRIC WIDTH (T TO T)	50 & 60 inch ( $\pm 0.5$ inch)	1270 & 1524 mm ( $\pm 12$ mm)
RESIN COMPATIBILITY	Polyester, Vinyl, Ester, Epoxy	Polyester, Vinyl, Ester, Epoxy
ROLL LENGTH	160 Feet (Min.:48 &Max.:175 Feet)	49 Meter (Min.:15 &Max.:53 Meter)
ROLL WEIGHT	199 & 217 Lbs. (Min.:60 & 65 & Max.:217 & 237 Lbs.)	90 & 98 Kg (Min.:27 & 29 & Max.: 98 & 107 kg)
PAPER CORE SIZE	3 -inch ID	76.2 mm ID
FRINGE LENGTH	0.5 inch ( $\pm 0.25$ inch)	12 mm ( $\pm 6$ mm)
ROLLS PER PALLETS	9 Rolls	9 Rolls

CONSTRUCTION	AREAL WEIGHT		TOLERANCE (%)	LINEAR WEIGHT	
	oz/sq.yd	g/sq.m		Yield (yd/lb)	Tex (g/km)
WR24(5x4)	23.50	797	$\pm 5$	225/225	2200/2200
CHOP	15.00	509	$\pm 8$	207	2400

\* Polyester weight not included

\* Each roll has a label in the core as well as one on the wrap outside.

### SKAPS INDUSTRIES

5549 State Road 425 Bypass, Henderson, KY 42420

Phone: (270) 827-8820, Fax: +1(706) 354 3737

Contact@Skaps.com

Rev :2/4/2021