

TECHNICAL DATA SHEET



PRODUCT CODE: KDB1200

Fabric Construction: 45° / -45° Biaxial knit Fabric

GLASS FIBER SPECIFICATION

GLASS TYPE	E Glass	
TOTAL AREA WEIGHT	12.08 oz/sq. yd (±5%)	410 g/sq.m (± 5%)
FABRIC WIDTH (T to T)	50 inch (±0.5 inch)	1270 mm ((±12 mm)
RESIN COMPATIBILITY	Polyester, Vinyl, Ester, Epoxy	Polyester, Vinyl, Ester, Epoxy
ROLL LENGTH	300 Feet (Min.:90 &Max.:315 Feet)	92 Meter (Min.:28 &Max.:96 Meter)
ROLL WEIGHT	104 Lbs. (Min.:31 &Max.:109 Lbs.)	47 Kg (Min.:14 & Max.: 49 kg)
PAPER CORE SIZE	3 -inch ID	76.2 mm ID
FRINGE LENGTH	0.5 inch (±0.25 inch)	12 mm ((±6 mm)
ROLLS PER PALLETS	16 Rolls	16 Rolls

CONSTRUCTION	AREAL WEIGHT		TOLERANCE (%)	LINEAR WEIGHT	
	oz/sq.yd	g/sq.m		Yield (yd/lb)	Tex (g/km)
45°	6.00	203	±5	1800	275
0°	0.04	1.36	±5	7300	68
90°	0.04	1.36	±5	7300	68
-45°	6.00	203	±5	1800	275

- * Polyester weight not included
- * Each roll has a label in the core as well as one on the wrap outside.

SKAPS INDUSTRIES

5549 State Road 425 Bypass, Henderson, KY 42420
Phone: (270) 827-8820, Fax: +1(706) 354 3737
Contact@Skaps.com

Rev :2/4/2021