

TECHNICAL DATA SHEET



PRODUCT CODE: KDBM2415

Fabric Construction: 45° / -45° Knit Biaxial with chop

GLASS FIBER SPECIFICATION

GLASS TYPE	E Glass	
TOTAL AREA WEIGHT	38.72 oz/sq. yd (±5%)	1313 g/sq.m (± 5%)
FABRIC WIDTH (T TO T)	50 inch (±0.5 inch)	1270 mm ((±12 mm)
RESIN COMPATIBILITY	Polyester, Vinyl, Ester, Epoxy	Polyester, Vinyl, Ester, Epoxy
ROLL LENGTH	200 Feet (Min.:60 &Max.:215 Feet)	61 Meter (Min.:18 &Max.:66 Meter)
ROLL WEIGHT	225 Lbs. (Min.:68 &Max.:243 Lbs.)	103 Kg (Min.:31 & Max.: 110 kg)
PAPER CORE SIZE	3 -inch ID	76.2 mm ID
FRINGE LENGTH	0.5 inch (±0.25 inch)	12 mm ((±6 mm)
ROLLS PER PALLETS	9 Rolls	9 Rolls

CONSTRUCTION	AREAL WEIGHT		TOLERANCE (%)	LINEAR WEIGHT	
	oz/sq.yd	g/sq.m		Yield (yd/lb)	Tex (g/km)
45°	11.82	401	±5	827	600
0°	0.04	1.36	±5	7300	68
90°	0.04	1.36	±5	7300	68
-45°	11.82	401	±5	827	600
Chop	15	509	±8	207	2400

* Polyester weight not included

* Each roll has a label in the core as well as one on the wrap outside.

SKAPS INDUSTRIES

5549 State Road 425 Bypass, Henderson, KY 42420

Phone: (270) 827-8820, Fax: +1(706) 354 3737

Contact@Skaps.com

Rev :2/4/2021