

TECHNICAL DATA SHEET



PRODUCT CODE: KLTDDB2600

Fabric Construction: QUADRAXIAL KNIT FABRIC

GLASS FIBER SPECIFICATION

GLASS TYPE	E Glass	
TOTAL AREA WEIGHT	25.49 oz/sq. yd ($\pm 5\%$)	864 g/sq.m ($\pm 5\%$)
FABRIC WIDTH (T TO T)	50 inch (± 0.5 inch)	1270 mm (± 12 mm)
RESIN COMPATIBILITY	Polyester, Vinyl, Ester, Epoxy	Polyester, Vinyl, Ester, Epoxy
ROLL LENGTH	300 Feet (Min.:90 &Max.:315 Feet)	92 Meter (Min.:28 &Max.:96 Meter)
ROLL WEIGHT	226 Lbs. (Min.:68 &Max.:237 Lbs.)	102 Kg (Min.:31 & Max.: 107 kg)
PAPER CORE SIZE	3 -inch ID	76.2 mm ID
FRINGE LENGTH	0.5 inch (± 0.25 inch)	12 mm (± 6 mm)
ROLLS PER PALLETS	9 Rolls	9 Rolls

CONSTRUCTION	AREAL WEIGHT		TOLERANCE (%)	LINEAR WEIGHT	
	oz/sq.yd	g/sq.m		Yield (yd/lb)	Tex (g/km)
0°	6.38	216	± 5	450	1100
45°	6.32	214	± 5	1800	275
90°	6.47	219	± 5	1200	410
-45°	6.32	214	± 5	1800	275

* Polyester weight not included

* Each roll has a label in the core as well as one on the wrap outside.

SKAPS INDUSTRIES

5549 State Road 425 Bypass, Henderson, KY 42420

Phone: (270) 827-8820, Fax: +1(706) 354 3737

Contact@Skaps.com

Rev :2/4/2021